




Assembly Instruction

CAUTION: Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

ITEM#:FLU4031A



Care and Cleaning



To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time: 20 minutes

Part List and Hardware List

| PIECE | DESCRIPTION | PICTURE | QUANTITY | PIECE | DESCRIPTION | PICTURE | QUANTITY |
|-------|----------------|---|----------|-------|--------------------|---|----------|
| A | mounting screw |  | 2X | H | bulb |  | 2X |
| B | Mounting Plate |  | 1X | I | finial |  | 2X |
| C | machine screw |  | 2X | J | Shade |  | 1X |
| D | ground screw |  | 1X | K | short threaded rod |  | 1X |
| E | wire connector |  | 3X | L | Glass |  | 1X |
| F | screwed ball |  | 2X | M | metal cover |  | 1X |

Installation


Step 1

Install the mounting plate(B) to the junction box with machine screw (C)


Step 2 Wire connection

Make wire connections, with wire connectors(E), following the reference chart listed below.

| Connect,Hot,Black or Red outlet Supply Wire to: | Connect,Neutral,White Outlet Supply Wire to: |
|---|---|
| Black | White |
| *Parallel Cord(round&smooth) | *Parallel Cord(square&ridged) |
| Clear,Brown,Gold or Black without Tracer(colored stripes) | Clear,Brown,Gold or Black without Tracer(colored stripes) |
| Insulated Wire(not green)with copper metal conductor | Insulated Wire(not green)with Silver metal conductor |



*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)



Grounding Instructions:

a) For installation in the United States: Wrap ground wire from outlet box around green ground screw on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.

b) For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.

Step 3

Install cage plate to the junction box with Mounting Screw (C),then fix it by turning screwed ball(F) clockwise.


Step 4

Insert the bulbs (H) into the sockets

Step 5

Fasten short threaded rod (K) on Shade (J) ,put glass(L) and matel cover(M) through short threaded rod (K) ,then fix by finial(I)

PLEASE USE TYPE"A" BULB MAX 40-WATT OR CFL BULB MAX 13-WATT OR LED BULB MAX 9-WATT
THERE ARE 2PCS LED 4-WATT BULB IN THE BOX



Step 6

Consult a qualified electrician to ensure correct branch circuit conductor.

ENJOY YOUR LAMP