




SAFAVIEH LIGHTING

Assembly Instruction

CAUTION: Read instruction carefully and turn electricity off at main circuit breaker panel before beginning installation.

ITEM#:LIT4448A



Care and Cleaning









To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.

To clear the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.

Do not use any cleaners with chemical, solvents or harsh abrasives. Use Only a dry soft cloth to dust or wipe carefully.

Estimated Assembly Time: 30 minutes


Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	Lamp Body		3X	E	Mounting Plate		2X
B	Shade		3X	F	Wire Nut		1X
C	Canopy Nut		1X	G	Canopy		1X
D	Wrench		6X	H	Mounting Screw		2X

Installation


Step 1

Unpack all parts from cartons carefully.
Using Wire nut(F) to connect wires



Step 2 Wire connection

Connect,Hot,Black or Red outlet Supply Wire to:	Connect,Neutral,White Outlet Supply Wire to:
Black	White
*Parallel Cord(round&smooth)	*Parallel Cord(square&ridged)
Clear,Brown,Gold or Black without Tracer(colored stripes)	Clear,Brwn,Gold or Black without Tracer(colored stripes)
Insulated Wire(not green)with copper metal conductor	Insulated Wire(not green)with Silver metal conductor



*Note: When parallel wire(SPTI&SPTII)is used. The neutral wire is square shaped and ridged and the hot wire will be round in shape and smooth.(See illustration on left)




Grounding Instructions:

- For installation in the United States: Wrap ground wire from outlet box around green ground screw (F) on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.
- For installation in Canada: If fixture is supplied with ground wire, wrap ground wire around green grounding screw on mounting bracket. Tighten ground screw.


Step 3

Fix the Mounting Plate(G) to the junction box with Mounting Screw (H).



Step 4

The adjustment or shortening of the lighting fixtures suspension length is only needed if the factory set cord length is not appropriate for your installation. Adjust the power cord length by loose the Allen Screw of the with the Wrench (D), tighten the screw if the cord length is desired.



Step 5

Attach the Canopy (D) to the junction box and fix it by turning the Canopy Nut (C).

Step 6

Install bulbs (A). Be sure to use bulb with wattage no greater than specified on this fixture

**PLEASE USE ON/OFF TYPE "B" BULB MAX 40-WATT OR CFL BULB MAX 9-WATT
THERE ARE 3PCS 25-WATT TYPE "B" BULB IN THE BOX**

Step 7

Consult a qualified electrician to ensure correct branch circuit conductor

ENJOY YOUR LAMP

