## **CARE AND MAINTENANCE**

Wipe clean with a soft, dry cloth. Test the cleaning method on a hidden area before using them over the entire area.

## NOTICE

- \* Please make sure that you have all parts indicated before you begin assembly of this item.
- \* This item should be assembled on a soft surface to prevent scratching the finished product during assembly.
- \* This item may require periodic tightening.
- \* Do not tighten bolts until completely assembled.


## **Part List and Hardware List**

PIECE	DESCRIPTION	PICTURE	QUANTITY
А	DRAWER		1 X
В	LEG		4 X
С	CROSS BAR		1 X
HW1	Hex Socket Bolt 1/4"-20 x 2"	0	8 X
HW2	Hex Socket Bolt 1/4"-20 x 3/8"	<b>©</b>	4 X
HW3	Allen Key 4mm		1 X



Model# NST6400

Product Dimensions: 19"W\*17"D\*25"H





Weight Capacity: 25 lbs


Warning: Do not stand on the product Warning: Do not over torque bolts


## **PREPARATION**


Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list. If any part is missing or damaged, do not attempt to assemble the product.

Estimated Assembly Time: 15 minutes.

Tools Required for Assembly (included): Allen Key







Step 1

Insert the protrusions on the 4\*Legs (B) into the tube of Cross bar (C). And use the Allen Key (HW3) to lock with 4\*Hex Socket Bolts (HW2).

Step 2

Attach the bottom side of Drawer (A) to the assembled metal base frame, And use the Allen Key (HW3) to lock with 8\*Hex Socket Bolts (HW1), as picture.

Step 3

Straighten up the assembled product, Assembly is completed.