WARNING

* Switch off the main electrical supply from the main fuse box / circuit breaker before installation.
* Inspect item carefully before attempting to install.
* If there is any damages or obvious defects, do not install.
* Item may not be returned once it has been installed.

CARE AND MAINTENANCE

* To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.
* To clean the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.
* Do not use any cleaners with chemical, solvents or harsh abrasives. Use only a dry soft cloth to dust or wipe carefully.

NOTICE& IMPORTANT SAFETY INSTRUCTIONS

** WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN **
* Please make sure that you have all parts indicated before you begin assembly of this item
* This item should be assembled on a soft surface to prevent scratching the finish during assembly
* To reduce the risk of fire, electrical shock or injury to persons or property, please follow the guideline below for safe use and installation
*The external flexible cable or cord of this lamp cannot be replaced
If the cord is damaged, the lamp shall be destroyed


Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	Plastic Expansion Screw		4X	I	Bulb		1X
B	Mounting Bracket		1X	J	Metal Connecting Rod		1X
C	Mounting Screw		4X	K	Mounting Screw		2X
D	Ground Screw		1X	L	Canopy A		1X
E	Wire Nut		3X	M	Nut and Gasket		1X
F	Mounting Screw		2X	N	Copper Screw		1X
G	Mounting Screw		4X	O	Canopy B		1X
H	Lamp Body		1X	P	Mounting Screw		1X

SAFAVIEH LIGHTING

Model#: PLT4084


Product Dimensions: 7"L x 9.5"W x 28.5"H




PREPARATION

* Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.
* If any part is missing or damaged, do not attempt to assemble the product.
* Estimated Assembly Time: 20 minutes.
* Tools Required for Assembly (not included): Screwdriver, Junction box
* If you are having difficulty, our friendly Customer Care team is always here to help. Please email **customersupport@safavieh.com**

NOTE: PLEASE USE TYPE"A" BULB MAX 60-WATT OR LED BULB MAX 9-WATT, THERE IS LED 4-WATT BULB IN THE BOX



Step 1: Install the Plastic Expansion Screw(A) on the wall, secure the Mounting Bracket(B) with Mounting Screw(C) and (F).



Step 2: Wire connection


Connect fixture neutral wire (ribbed) to the outlet box neutral wire (usually white) using a wire nut.
Connect fixture hot wire (smooth with markings) to the outlet box hot wire (usually black) using a wire nut.
CAUTION: Do not reverse the hot and neutral connections

Grounding Instructions:


Wrap ground wire from outlet box around green ground screw on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire nut.

PREPARATION


* Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.
* If any part is missing or damaged, do not attempt to assemble the product.
* Estimated Assembly Time: 20 minutes.
* Tools Required for Assembly (not included): Screwdriver, Junction box
* If you are having difficulty, our friendly Customer Care team is always here to help. Please email **customersupport@safavieh.com**




Step 3: Lock the Ground Screw(D) and Wire Nut(E), install the Lamp Body(H) to the Mounting Bracket(B) and secure with the Mounting Screw(G).



Step 4: Install the Bulb(I) to the sockets.



Step 5: Install the Metal Connecting Rod(J) on the Lamp Body(H) and lock with the Mounting Screw(K), then put the Canopy A(L) and lock with the Nut and Gasket(M).



Step 6: Put the Copper Screw(N) on the Canopy A(L) first, and then put the Canopy B(O), finally lock with the Mounting Screw(P).